

(11)Publication number:

2002-272705

(43)Date of publication of application: 24.09.2002

(51)Int.CI.

A61B 5/055 GO1R 33/3415

G01R 33/48

(21)Application number : 2002-033293

(71)Applicant: SIEMENS AG

(22)Date of filing:

12.02.2002

(72)Inventor: IANMIN WANG

(30)Priority

Priority number : 2001 10106830

Priority date : 14.02.2001

Priority country: DE

(54) MAGNETIC RESONANCE IMAGE FORMATION METHOD

(57)Abstract:

PROBLEM TO BE SOLVED: To simply obtain a sensitivity profile of an individual antenna in an antenna array.

SOLUTION: A total image 26 is obtained by sending a high frequency excitation pulse and a gradient magnetic field pulse to an imaging space, generating spatial-coded magnetic resonance signals, receiving the magnetic resonance signals by receiving antennas 6A to 6D, forming k space data records 12A to 12D having outside space lines 14A to 14D and more tightly arranged central specifical space. k space lines 16A to 16D from the reception signal of each of the receiving antennas 6A to 6D, reconstructing one intermediate images 20A to 20D from each of the k space data records 12A to 12D, determining sensitivity

profiles 22A to 22D from the central k space data line 16A to 16D, and combining intermediate images 20A to 20D in connection with the sensitivity profiles 22A to 22D.

LEGAL STATUS



[Date of request for examination]

03.02.2005

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office